







451 BL 1/3D - ATEX EXPLOSION PROOF















Weight

- ✓ Largest surface filter in its category
- ✓ Complete steel construction
- ✓ Extractable collection container with optional use of disposable bags
- ✓ Compact and mobile
- ✓ Easy filter replacement

- ✓ Stainless steel AISI304 collection tank
- ✓ Motor with very long service life
- ✓ Pressure relief valve for motor protection
- ✓ ATEX certified for Zone 20 inside the chamber and for Zone 22 outside the chamber

| SUCTION UNIT | | |
|---------------------------|--------|----------------------------------|
| Atex zones | | ATEX Z20/21 |
| Marking | | II 1/2D Ex h tb IIIC T95°C Da/Db |
| Voltage | V - Hz | 115/230 - 50/60 1~ |
| Power | kW | 1,1 |
| Max water lift | mmH□O | 2,250 |
| Max air flow | m³/h | 215 |
| Suction inlet | mm | 80 |
| Noise level (EN ISO 3744) | dB(A) | 74 |

| FILTER UNIT | | |
|-----------------------|----------------|-------------------|
| Filter Type | | Star |
| Surface - Diameter | cm²-mm | 20.000 - 420 |
| Material - Efficiency | IEC 60335-2-69 | Polyester - ANT M |
| Cleaning system | | Dustop |
| | | |

| COLLECTION UNIT | | |
|--------------------|------|------------|
| Transport capacity | kg/h | 45 |
| VOLUME | | |
| Dimensions | cm | 58x62x138h |

57





The motor head is equipped with a Brushless motor: the lack of carbons allows the use of the machine even in explosive hazardous areas. The motor is protected by a series of filters and it is turned on by an independent switch placed on a soundproofed and robust metal motor head.

The motor head includes a vacuum gauge and tension power lights as standard.



FILTER UNIT

A vacuum gauge enables to check constantly the state of the filter and detect possible clogging, warning the operator that the filter must be cleaned.

The antistatic polyester cartridge filter placed inside the filter chamber guarantees a large filter surface and prevents the clogging of the filter.

It is possible to clean the filter using an integrated mechanical system: an external lever shakes the filter vertically and enables to clean the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.



COLLECTION UNIT

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels, that make it suitable for mobile service even when used on rough surfaces.

The vacuumed material is placed inside an AISI304 stainless steel drop-down bin mounted on wheels, which makes it possible to dispose easily and safely of the vacuumed material.