

DBFV 30 - INDUSTRIAL THREE PHASE



FOOD INDUSTRY



CHEMICAL-PHARMACEUTICAL



PACKAGING



COFFEE , TEA, TOBACCO PROCESSING



- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- ✓ Easy filter replacement
- ✓ Integrated filter cleaning system
- ✓ Reduced downtime of machine tools
- ✓ Pressure relief valve for motor protection
- ✓ Possibility of integration on other vacuum cleaners
- ✓ Low noise level
- ✓ Full customization for specific needs



SUCTION UNIT

Voltage	V - Hz	400 - 50 3~
Power	kW	2,2
Electrical protection	IP	65
Max water lift	mmH ₂ O	2600
Max air flow	m ³ /h	318
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	70



FILTER UNIT

Filter Type		Star
Surface - Diameter	cm ² -mm	8.000 - 360
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Cleaning system		Manual



COLLECTION UNIT

Capacity	l	25
----------	---	----



VOLUME

Dimensions	cm	54x55x103h
Weight	kg	60



SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.

A pressure relief valve protects the motor, providing additional air for cooling.



FILTER UNIT

The large surface star antistatic filter, located inside the filter chamber, is made of polyester and provides high resistance against clogging and passage of fine dust. It is possible to clean the filter using an integrated mechanical system: an external lever shakes the filter vertically and enables to clean the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.



COLLECTION UNIT

The unit is manufactured with thick painted steel for improved sturdiness and long-lasting lifetime



OPTIONALS

- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ EARTH GROUNDING
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST