





452 AIR 2V - AIR POWERED











- ✓ Complete steel construction
- ✓ Extractable collection container with optional use of disposable bags
- ✓ Compact and mobile
- ✓ High filtration efficiency

- ✓ Compressed air supply through a double Venturi suction unit
- ✓ Easy to handle
- ✓ Large surface antistatic filter
- ✓ Low noise level

SUCTION UNIT		
Air supply	I / min	3.000
Air supply pressure	bar	6
Ø Air supply hose	mm	16
Max water lift	mmH□O	4.180
Max air flow	m³/h	300
Noise level (EN ISO 3744)	dB(A)	73

FILTER UNIT		
Filter Type		Star
Surface - Diameter	cm²-mm	20.000 - 420
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Cleaning system		Manual
COLLECTION UNIT		

Capacity	lt	45
VOLUME		
Dimensions	cm	55x62x119h
Weight	kg	49





SUCTION UNIT

The suction is provided by two venturi compressed-air-driven suction units, protected inside a strong steel chassis, which contains also sound absorbing material to minimize noise during service. The suction is developed by a venturi-type vented suction unit, protected inside a solid steel head, containing sound absorbing material that minimizes noise during service.

The head includes a pressure and a vacuum gauge, in order to detect the clogging of the filter



FILTER UNIT

The large surface star filter, located inside the filter stainsteel chamber, is made of polyester and provides high resistance against clogging and passage of fine dust. It is possible to clean the filter using an integrated mechanical system: an external lever shakes the filter vertically and enables to clean the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.



COLLECTION UNIT

The detachable AISI 304 steel collection tank has a quick release system for the rapid disposal of the vacuumed material.



OPTIONALS

- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ PTFE COATED FILTER CLASS M
 - HEAT RESISTANT FILTER (UP TO 250° CELSIUS)
- ✓ STAINLESS STEEL COLLECTION TANK
- STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ CYCLONE FOR FILTER PROTECTION
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST