

MTL 202 DS OVEN - INDUSTRIAL SINGLE PHASE



CERAMICS AND POTTERY INDUSTRIES



CLEANING CONTRACTORS



WASTE TREATMENT - RECYCLING



ADDITIVE MANUFACTURING



- ✓ Largest surface filter in its category
- ✓ Two powerful by pass motors with independent cooling
- ✓ Compact and mobile
- ✓ Easy filter replacement
- ✓ Accessory kit as standard
- ✓ Dustop filter cleaning system
- ✓ Easily removable container for safe disposal of collected material



SUCTION UNIT

Voltage	V - Hz	230 - 50 1~
Power	kW	2,3
Max water lift	mmH ₂ O	2.500
Max air flow	m ³ /h	360
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	76



FILTER UNIT

Filter Type		Bag
Surface - Diameter	cm ² -mm	360 - 2.650
Material - Efficiency	IEC 60335-2-69	NOMEX
Cleaning system		Dustop



COLLECTION UNIT

Capacity	l	20
----------	---	----



VOLUME

Dimensions	cm	59x48x110h
Weight	kg	35



SUCTION UNIT

The suction is provided by two by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.



FILTER UNIT

Inside the filtering chamber there is a Nomex polyester filter resistant to temperatures up to 200 °

It is possible to clean the filter using the Dustop, an integrated reverse pulse system: by closing the suction inlet and opening a flap in the filter chamber, the airflow generated by the motor cleans the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.



COLLECTION UNIT

The detachable AISI 304 steel collection tank has a quick release system for the rapid disposal of the vacuumed material.



OPTIONALS

- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ ANTISTATIC FILTER CLASS M
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ EARTH GROUNDING