

DG 200 PN - INDUSTRIAL THREE PHASE



CEMENT



BUILDING AND CONSTRUCTION



ELECTRONICS



RUBBER



PACKAGING



- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- ✓ Tangential suction inlet with integrated separation cyclone
- ✓ Complete steel construction
- ✓ Pressure relief valve for motor protection
- ✓ Vacuum gauge to detect filter clogging
- ✓ Hour meter for planned maintenance
- ✓ Star-triangle switchboard
- ✓ Reduced downtime of machine tools
- ✓ High filtration efficiency
- ✓ Integrated automatic filter cleaning system



SUCTION UNIT

Voltage	V - Hz	400 - 50 3~
Power	kW	18,5
Electrical protection	IP	65
Max water lift	mmH ₂ O	4400
Max air flow	m ³ /h	1350
Suction inlet	mm	120
Noise level (EN ISO 3744)	dB(A)	77



FILTER UNIT

Filter Type	Cartridge	
Surface - Diameter	cm ² -mm	260000
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Air load on filter	m ³ /m ² /h	52
Cleaning system	Automatic PN	
Cartridge number	4	



COLLECTION UNIT

Capacity	l	220
----------	---	-----



VOLUME

Dimensions	cm	92x220x220h
Weight	kg	685



SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.

A pressure relief valve protects the motor, providing additional air for cooling.



FILTER UNIT

A vacuum gauge enables to check constantly the state of the filter and detect possible clogging, warning the operator that the filter must be cleaned.

The suction inlet is tangential, with an internally welded cyclone that deflects the incoming material.

The polyester cartridges inside the filter chamber guarantee large filter surface and prevent filter clogging.

Cartridges are automatically cleaned by a pneumatic reverse pulse cleaning system. The system is automatic, timed and adjustable. A compressor can be installed (on demand) on the back frame to guarantee the required air supply.



COLLECTION UNIT

The vacuumed material sets down into the container equipped with castors. Thanks to the safe and complete frontal discharge it's easy to empty the container without get in contact with dirt. The industrial vacuum is mounted on a robust epoxy painted chassis, with polyurethane castors and forklift intakes.



OPTIONALS

- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ EARTH GROUNDING
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST
- ✓ PTFE COATED FILTER CLASS M
- ✓ REMOTE CONTROL