





MTL 501 WD - PROFESSIONAL WET & DRY



FOOD INDUSTRY





CLEANING CONTRACTORS



VEHICLE - TRANSPORT CLEANING





- ✓ Complete steel construction
- ✓ Compact and mobile
- ✓ Easy filter replacement

- ✓ Floating device to stop the suction when container is full
- ✓ Discharge hose for liquids
- ✓ Accessory kit as standard

SUCTION UNIT		
Power	kW	1,15
Max water lift	mmH□O	2.500
Max air flow	m³/h	180
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	74
Voltage	V - Hz	230 - 50 1~
FILTER UNIT		
Filter Type		Star

COLLECTION UNIT		
Discharge system		
Capacity	I	50

VOLUME		
Dimensions	cm	52x40x90h
Weight	kg	28





SUCTION UNIT

The suction is made by a carbon brush by-pass motor which is activated by an independent switch placed inside a robust metal motor head. The motor head is soundproofed by sound-absorbent material.



FILTER UNIT

A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.

A propylene filter for liquids is installed upstream. This filter guarantees the efficient filtration of the vacuumed oil; an additional plastic foam filter prevents most of the liquid mist from getting to the motor.



COLLECTION UNIT

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels, that make it suitable for mobile service even when used on rough surfaces.



- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST
- ✓ STAINLESS STEEL COLLECTION TANK