


## TC 220 IF - OIL AND CHIPS



METALWORKING



- ✓ Reduced downtime of machine tools
- ✓ Reduction of disposal costs due to exhausted oils
- ✓ Reduction of machineries cleaning times
- ✓ A turnable suction inlet simplifies vacuuming operations
- ✓ A window allows to inspect and access the collection tank
- ✓ Floating device to stop the suction when container is full
- ✓ Grid for chips vacuuming



### SUCTION UNIT

Voltage	V - Hz	400 - 50 3~
Power	kW	3
Max water lift	mmH <sub>2</sub> O	3000/2700
Max air flow	m <sup>3</sup> /h	318
Noise level (EN ISO 3744)	dB(A)	78



### FILTER UNIT

Filter Type	3D SuperWeb
Media - Filtration	Polypropylene - 20µm



### COLLECTION UNIT

Discharge system		
Liquids capacity	l	220
Solids capacity	l	40
Discharge speed	l / min	200

Floating device



### VOLUME

Dimensions	cm	145x72x175h
Weight	kg	185



## SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.

A pressure relief valve protects the motor, providing additional air for cooling.



## FILTER UNIT

A propylene filter for liquids is installed upstream. This filter guarantees the efficient filtration of the vacuumed oil; an additional plastic foam filter prevents most of the liquid mist from getting to the motor.

SUPERWEB 3D primary filter is a special and hydro-oleophobic filter which guarantees the maximum oil separation while protecting the engine from oily mists and atmospheric dust



## COLLECTION UNIT

Forklift intakes for easy discharge.

The vacuumed liquid can be discharged quickly by means of a reversed airflow system, which can be activated by rotating a knob



## OPTIONALS

- ✓ OIL & WATER PROOF CARTRIDGE
- ✓ PPL OIL FILTRATION KIT DOWN TO 300 MICRON (SUCTION)