

MTL 802 WXP - INDUSTRIAL SINGLE PHASE



OEM ORIGINAL EQUIPMENT MANUFACTURER



BUILDING AND CONSTRUCTION



WINE



CLEANING CONTRACTORS



SURFACE PREPARATION



- ✓ Two powerful by pass motors with independent cooling
- ✓ Compact and mobile
- ✓ PPL filter for chips separation
- ✓ Discharge hose for liquids
- ✓ Accessory kit as standard
- ✓ Submerged pump for the discharge of the sucked liquid
- ✓ Stainless steel AISI304 collection tank
- ✓ Simultaneous operation of liquids vacuuming and discharge



SUCTION UNIT

Voltage	V - Hz	230 - 50 1~
Power	kW	2,3
Max water lift	mmH ₂ O	2.500
Max air flow	m ³ /h	360
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	76



FILTER UNIT

Media - Filtration	Polypropylene - 300µm
--------------------	-----------------------



COLLECTION UNIT

Discharge system	
Capacity	l
	80



VOLUME

Dimensions	cm	53x59x105h
Weight	kg	50



SUCTION UNIT

The suction is provided by two by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.



FILTER UNIT

A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.



COLLECTION UNIT

The vacuum cleaner is mounted on a solid steel trolley, provided with a support for hoses when not used, and equipped with oil proof wheels and braking castors.

The AISI 304 stainless steel collection tank has a quick system for the rapid disposal of the vacuumed material.

The filtered liquid can be discharged easily and quickly thanks to a submersible pump



OPTIONALS

✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST