







MTL 302 ACD - ACD











- ✓ Compact and mobile
- ✓ Easy filter replacement
- \checkmark Easy to clean and to maintain
- ✓ Accessory kit included

- ✓ Stainless steel AISI304 collection tank
- ✓ Large surface antistatic filter
- ✓ Vacuum powerhead Ex tb Dust Tight IP64 certified
- ✓ ATEX accessories and non-metallic parts tested

SUCTION UNIT		
Voltage	V - Hz	230 - 50/60 1~
Power	kW	2,2
Max water lift	mmH□O	2.500
Max air flow	m³/h	360
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	74
Marking	II 1/-D Ex h IIIC T80°C (Internal) Da/-	
Atex zones		ACD EX 1/- D

FILTER UNIT		
Filter Type		Star
Surface - Diameter	cm²-mm	4.000 - 360
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Secondary filter		HEPA

COLLECTION UNIT		
Capacity	I	40

cm	44x42x78h
kg	25





SUCTION UNIT

The suction is provided by two by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.



FILTER UNIT

The large surface star antistatic filter, located inside the filter chamber, is made of polyester and provides high resistance against clogging and passage of fine dust.



COLLECTION UNIT

The vacuumed material is placed inside an AISI304 stainless steel drop-down bin mounted on wheels, which makes it possible to dispose easily and safely of the vacuumed material.