



802 WD AIREX 2V - AIR POWERED EXPLOSION PROOF



OEM ORIGINAL EQUIPMENT MANUFACTURE



ELECTRONICS



OPTICS



PLASTICS



- ✓ Vacuum gauge to detect filter clogging
- ✓ Compact and mobile
- ✓ Easy filter replacement
- ✓ Floating device to stop the suction when container is full

- ✓ Discharge hose for liquids
- ✓ Compressed air supply through a double Venturi suction unit
- ✓ Earth grounding
- ✓ Certificate for use in ATEX 1,2,21 and 22 areas

SUCTION UNIT

Atex zones		ATEX Z1-2/21-22
Marking		Ex II 2D Ex h IIIC T85°C Db - Ex II 2G Ex
Air supply	l / min	3000
Air supply pressure	bar	6
Ø Air supply hose	mm	16
Max water lift	mmH ₂ O	4180
Max air flow	m ³ /h	300
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	73

FILTER UNIT

Filter Type		Bag
Surface - Diameter	cm ² -mm	8.000 - 420
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M

COLLECTION UNIT

Capacity	lt	80
----------	----	----

VOLUME

Dimensions	cm	62x53x108h
Weight	kg	36



SUCTION UNIT

The suction is provided by two venturi compressed-air-driven suction units, protected inside a strong steel chassis, which contains also sound absorbing material to minimize noise during service. The suction is developed by a venturi-type vented suction unit, protected inside a solid steel head, containing sound absorbing material that minimizes noise during service.

The head includes a pressure and a vacuum gauge, in order to detect the clogging of the filter



FILTER UNIT

A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.

A propylene filter for liquids is installed upstream. This filter guarantees the efficient filtration of the vacuumed oil; an additional plastic foam filter prevents most of the liquid mist from getting to the motor.

The dust filter is made of a double bag (polyester + nylon) and has a self cleaning system working on the pressure difference principle.



COLLECTION UNIT

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels, that make it suitable for mobile service even when used on rough surfaces.



OPTIONALS

- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ ACTIVATED CARBON FILTER