



XTRACTOR 2BL - INDUSTRIAL SINGLE PHASE



CEMENT



BUILDING AND CONSTRUCTION



- ✓ Keeps the workplace clean
- ✓ Easy to handle
- ✓ Easy to connect to floor preparation machinery
- ✓ Suitable for continuous use 24/7
- ✓ Integrated automatic filter cleaning system
- ✓ Standard or Endless Bag interchangeable collection unit
- ✓ System of springs allows to reduce the height of the vacuum of 25cm
- ✓ Endless Bag



SUCTION UNIT

Voltage	V - Hz	230 - 50 3~
Power	kW	2.2
Max water lift	mmH ₂ O	2250
Max air flow	m ³ /h	430
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	75



FILTER UNIT

Filter Type	Cartridge	
Surface - Diameter	cm ² -mm	57.000
Material - Efficiency	IEC 60335-2-69	Polyester - M PTFE
Cleaning system	Automatic PN	



COLLECTION UNIT

Capacity	lt	Longopac 20mt
----------	----	---------------



VOLUME

Dimensions	cm	65x91x198/172h
Weight	kg	145



SUCTION UNIT

The suction unit is equipped with 2 Brushless motors that allow the machine to be used in maximum safety even in areas at risk of explosion thanks to the absence of charcoal. The motors are soundproofed and protected by different levels of filtration. The motors are powered by two independent switches and it is possible to adjust the suction performance by using a potentiometer located on the head.



FILTER UNIT

Les cartouches en polyester à l'intérieur de la chambre filtrante garantissent une large surface de filtration et préviennent le colmatage des filtres.

Cartridges are automatically cleaned by a pneumatic reverse pulse cleaning system. The system is automatic, timed and adjustable. A compressor placed on the back frame guarantees the required air supply.



COLLECTION UNIT

The vacuumed material is discharged inside a 20 mt Endless Bag ; when the extremity of the bag is full, the operator can seal and dispose that part of the bag in total security, without coming in contact with dusts and spreading them in the environment