

XTRACTOR 3BP - INDUSTRIAL SINGLE PHASE



BUILDING AND CONSTRUCTION



SURFACE PREPARATION



- ✓ Keeps the workplace clean
- ✓ Easy to handle
- ✓ Easy to connect to floor preparation machinery
- ✓ Integrated automatic filter cleaning system
- ✓ Endless Bag
- ✓ Complete steel construction
- ✓ Compact and mobile



SUCTION UNIT

Voltage	V - Hz	230 - 50 1~
Power	kW	3,45
Max water lift	mmH ₂ O	2.500
Max air flow	m ³ /h	540
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	70



FILTER UNIT

Filter Type	Cartridge	
Material - Efficiency	IEC 60335-2-69	Polyester - M PTFE
Cleaning system	Automatic PN	
Surface	cm ²	57.000



COLLECTION UNIT

Capacity	l	Endless Bag 20mt
----------	---	------------------



VOLUME

Dimensions	cm	65x91x190/164h
Weight	kg	140



SUCTION UNIT

The suction is provided by three by-pass motors, using carbon brushes and placed inside a sturdy steel casing filled with soundproofing material.



FILTER UNIT

The polyester cartridges inside the filter chamber guarantee large filter surface and prevent filter clogging.

Cartridges are automatically cleaned by a pneumatic reverse pulse cleaning system. The system is automatic, timed and adjustable. A compressor placed on the back frame guarantees the required air supply.



COLLECTION UNIT

The vacuumed material is discharged inside a 20 mt Endless Bag; when the extremity of the bag is full, the operator can seal and dispose that part of the bag in total security, without coming in contact with dusts and spreading them in the environment



OPTIONALS

✓ ABSOLUTE HEPA FILTER /H14