



301-302 TORCH - INDUSTRIAL SINGLE PHASE



BUILDING AND CONSTRUCTION



ELECTRONICS



OPTICS



- ✓ Optional articulated arm to suction in a restricted area
- ✓ Suction directly from the MIG/MAG welding torch

- ✓ Dustop filter cleaning system



SUCTION UNIT

Voltage	V - Hz	230 - 50 1~
Power	kW	1,15 - 2,3
Max water lift	mmH ₂ O	2.500
Max air flow	m ³ /h	180 - 360
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	74 - 76



FILTER UNIT

Prefilter		Spark trap filter
Filter Type		Cartridge
Surface - Diameter	cm ² -mm	7.500 - 245
Material - Efficiency	IEC 60335-2-69	Polyester - M
Cleaning system		Dustop
Secondary filter		HEPA



COLLECTION UNIT

Capacity	l	13
----------	---	----



VOLUME

Dimensions	cm	40x50x86h
Weight	kg	25



SUCTION UNIT

The suction unit is made of an electric fan which guarantees elevated air flow.



FILTER UNIT

It is possible to clean the filter using the Dustop, an integrated reverse pulse system: by closing the suction inlet and opening a flap in the filter chamber, the airflow generated by the motor cleans the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.



OPTIONALS

- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ ACTIVE CARBON FILTER