



## 301-302 TORCH - INDUSTRIAL SINGLE PHASE



BUILDING AND CONSTRUCTION



ELECTRONICS



OPTICS



- ✓ Optional articulated arm to suction in a restricted area
- ✓ Suction directly from the MIG/MAG welding torch

- ✓ Dustop filter cleaning system



### SUCTION UNIT

Voltage	V - Hz	230 - 50 1~
Power	kW	1,15 - 2,3
Max water lift	mmH <sub>2</sub> O	2.500
Max air flow	m <sup>3</sup> /h	180 - 360
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	74 - 76



### FILTER UNIT

Prefilter	Spark trap filter	
Filter Type	Cartridge	
Surface - Diameter	cm <sup>2</sup> -mm	7.500 - 245
Material - Efficiency	IEC 60335-2-69	Polyester - M
Cleaning system	Dustop	
Secondary filter	HEPA	



### COLLECTION UNIT

Capacity	l	13
----------	---	----



### VOLUME

Dimensions	cm	40x50x86h
Weight	kg	25



## SUCTION UNIT

The suction unit is made of an electric fan which guarantees elevated air flow.



## FILTER UNIT

It is possible to clean the filter using the Dustop, an integrated reverse pulse system: by closing the suction inlet and opening a flap in the filter chamber, the airflow generated by the motor cleans the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.



## OPTIONALS

- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ ACTIVE CARBON FILTER