



B200 M - INDUSTRIAL SINGLE PHASE



FOOD INDUSTRY



CHEMICAL-PHARMACEUTICAL



ELECTRONICS



METALWORKING



- ✓ Complete steel construction
- ✓ Three powerful by pass motors with independent cooling
- ✓ Compact and mobile
- ✓ Filtration and recovery of cutting oil and coolant liquid
- ✓ Modularity is guaranteed to fulfil the client's needs
- ✓ Full customization for specific needs



SUCTION UNIT

Voltage	V - Hz	230 - 50 1~
Power	kW	3
Max water lift	mmH ₂ O	2400
Max air flow	m ³ /h	540
Suction inlet	mm	90
Noise level (EN ISO 3744)	dB(A)	77



FILTER UNIT

Filter Type		Star
Surface - Diameter	cm ² -mm	12000 - 500
Material - Efficiency	IEC 60335-2-69	Polyester - L
Air load on filter	m ³ /m ² /h	500
Cleaning system		Manual



COLLECTION UNIT

Discharge system		
Liquids capacity	l	30
Solids capacity	l	200



VOLUME

Dimensions	cm	93x81x124h
Weight	kg	160



SUCTION UNIT

The suction is provided by three by-pass motors, using carbon brushes and placed inside a sturdy steel casing filled with soundproofing material.



FILTER UNIT

The large surface star filter, located inside the filter stainless steel chamber, is made of polyester and provides high resistance against clogging and passage of fine dust.



COLLECTION UNIT

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels, that make it suitable for mobile service even when used on rough surfaces.

The container is compact and contains the sieve grid which retains the solid part.



OPTIONALS

✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST