

CE



COPYRIGHT © 2023 DELFIN S.R.L. ALL RIGHTS RESERVED COPYRIGHT © 2023 DELFIN S.R.L. TUTTI I DIRITTI RISERVATI

TECH420E D100 15kW - PNEUMATIC CONVEYOR





CHEMICAL-PHARMACEUTICAL



COFFEE, TEA, TOBACCO PROCESSING







and maintenance costs

✓ Improved hygiene and operational conditions

✓ The system includes a side channel blower, which is a silent, powerful three-phase motor

which requires no maintenance



- ✓ Customization and configuration available according to specific needs
- ✓ Easy to install, turn on, use and sanitize
- ✓ No obstruction or environmental pollution
- ✓ CE-certified, FDA-certified system for food application. A wide range of optional accessories is available
- ✓ Increased productivity

Max load Ø P. conv ✓ Low economic impact and reduced operating Dimensio ✓ Product quality and integrity preservation

SUCTION	UNIT				
Voltage			V - Hz		230-50 1~
Power			kW		15
Max air flow			m³/h		720
Max. waterlift			mbar		530
FILTER UI	NIT				
Material - Efficiency	/		IEC 60335-2-69	P	olyester - ANT M
Air cleaning consur	nption		Nl/min		350
DISCHAR	GE UNIT				
Ø Unload / Outlet []		mm		150 -250
Type of unloading					Clapet valve
	5 UNIT				
Weight			kg		28
Max load volume			lt		20
Ø P. conveying syst	tem 🛛		mm		100 - 80
Dimensions			cm		Ø420 - h980
Transport capacity	kg/h	3.700	2.200	1.300	650
Distance	Mt	10	15	20	25

All data mentioned in this document may change without notice Tutti i dati riportati in questo documento potrebbero variare senza avviso



SUCTION UNIT

High efficiency suction unit with side channel blower, a three-phase electrical engine with no need of maintenance and very suitable for continuous and long-term use. It includes by-pass valves and a choke valve.

FILTER UNIT

Filter unit: an antistatic polyester cartridge for food application, FDA-certified, 1µm filter media. Static and automatic filter cleaning system

DISCHARGE/LOAD UNIT

Single-piece truncated cone shape loading unit with tangential inlet Unloading unit with clapet



Control unit: electrical panel with PLC 12I-8O placed 3meters away from the loading unit

AVAILABLE ACCESSORIES

- ✓ FDA-Certified flexible hose
- ✓ Suction lance
- Pick-up hopper

- ✓ AISI316 STAINLESS STEEL COMPONENTS
- ✓ PNEUMATIC VIBRATOR
- ✓ RELIEF VALVE TO EMPTY THE PRODUCT LINE
- ✓ PARTS IN CONTACT WITH MIRROR POLISHING
- ✓ KIT FOR THE ASSEMBLY OR THE CONNECTION TO OTHER SYSTEMS