

AS70-002

WHEELED SCRAP COLLECTOR FOR LARGE QUANTITIES OF CUT-OFFS AND MANUFACTURING SCRAP



Filter category:



FEATURES

Extraction of production waste directly from production/ packaging machinery and the textile industry

Compact, stable and mobile

Complete painted steel construction

Nylon Bag

Motor requiring no routine maintenance, suitable for continuous 24/7 operation

TECHNICAL DATA

		AS70-002
Voltage	V	400
Power	kW	6.3
Frequency	Hz	50
Current draw	A	11.8
Suction inlet diameter	mm	80
Tank capacity	L.	210
Noise level	dB(A)	71
Dimensions	cm	65x130x130h
Weight	kg	125
Electrical protection	IP	65
Maximum vacuum	mmH2O	3600
Continuous waterlift	mmH2O	3200
Maximum air flow	m ³ /h	530
Motor Type		Three-phase Turbine
Primary filter		Star
Primary filter diameter	mm	360
Primary filter media		Antistatic polyester
Filter class (IEC 60335-2-69) primary filter		M
Filter cleaning system		Manual
Absolute HEPA Filter		Optional
Filter area of the absolute filter	cm ²	20500
Absolute filter class (EN 1822-5)		H14 with 99.995% efficiency according to the MPPS method

OPTIONAL

Code	Description
MT	Earth Grounding
XX/IP	Mirror polishing of the internal chamber
SB	Safe bagging system (1 bag)
SP	Single-phase suction unit



COPYRIGHT 2026 DELFIN S.R.L. ALL RIGHTS RESERVED
COPYRIGHT 2026 DELFIN S.R.L. ALL RIGHTS RESERVED

MACHINE CODE	DESCRIPTION
AS70-002	AS70 X (AISI 304 container only)

All data mentioned in this document may change without notice. All data contained in this document is subject to change without notice.

DELFIN
FOR A DUST-FREE WORLD

www.delfinvacuums.com
delfin@delfinvacuums.it