



DM3ELLPAUT-001

SINGLE-PHASE VACUUM CLEANER WITH SAFE BAGGING AND CONTINUOUS FILTER CLEANING



Filter category:



FEATURES

Dust and solids

Compact and mobile

Complete painted steel construction

Cartridges with integrated ClearAut and Dustop automatic cleaning systems

Extremely versatile

All data mentioned in this document may change without notice. All data contained in this document is subject to change without notice.

DELFIN
FOR A DUST-FREE WORLD
www.delfinvacuums.com
delfin@delfinvacuums.it

COPYRIGHT 2026 DELFIN S.R.L. ALL RIGHTS RESERVED
COPYRIGHT 2026 DELFIN S.R.L. ALL RIGHTS RESERVED

TECHNICAL DATA

 **OPTIONAL**

		DM3ELLPAUT-001
Voltage	V	230
Power	kW	3.45
Frequency	Hz	50
Current draw	A	15
Suction inlet diameter	mm	80
Tank capacity	L.	20 m Endless bag
Noise level	dB(A)	76
Dimensions	cm	86x78x166h
Weight	kg	80
Maximum vacuum	mmH2O	2500
Continuous waterlift	mmH2O	2500
Maximum air flow	m ³ /h	540
Motor Type		Single-phase Bypass
Primary filter		2x cartridges
Primary filter surface area	cm ²	30000
Primary filter diameter	mm	360
Primary filter media		Polyester
Filter class (IEC 60335-2-69) primary filter		M PTFE
Filter cleaning system		Automatic ClearAut + Dustop
E10 filter		Included
Filter surface area	cm ²	26000
Filter class (EN 1822-5)		H14 with 99.995% efficiency according to the MPPS method

Code	Description
H	Additional H14 absolute filter



COPYRIGHT 2026 DELFIN S.R.L. ALL RIGHTS RESERVED
COPYRIGHT 2026 DELFIN S.R.L. ALL RIGHTS RESERVED

MACHINE CODE	DESCRIPTION
DM3ELLPAUT-001	DM3 EL AUT ENDLESS BAG

All data mentioned in this document may change without notice. All data contained in this document is subject to change without notice.

DELFIN
FOR A DUST-FREE WORLD

www.delfinvacuums.com
delfin@delfinvacuums.it