


# LC1000 D

INDUSTRIAL VACUUM CLEANER FOR CLEANROOM



Filter category:



## FEATURES

Dust / Solids

Very compact and extremely easy to transport

stainless steel construction

Multiple stages of filtration, perfectly clean air exiting the extractor

Compliant up to ISO 4, compliant with GMP standards, easy to clean and disinfect: autoclavable (up to 120°C, excluding the Motor head)

## TECHNICAL DATA

 OPTIONAL

		LC1000D-001
Voltage	V	230
Power	kW	1
Frequency	Hz	50
Current draw	A	5
Suction inlet diameter	mm	40
Tank capacity	L.	5
Noise level	dB(A)	70
Dimensions	cm	42x35x50h
Weight	kg	20
Solids capacity	L	5
Maximum vacuum	mmH2O	2900
Continuous waterlift	mmH2O	2900
Maximum air flow	m <sup>3</sup> /h	175
Motor Type		Through Flow Motor
Primary filter		Bag
Primary filter surface area	cm <sup>2</sup>	2000
Primary filter diameter	mm	280
Primary filter media		Polyester
Filter class (IEC 60335-2-69) primary filter		M PTFE
Absolute HEPA Filter		In suction: Standard In blowing: Standard



COPYRIGHT 2026 DELFIN S.R.L. ALL RIGHTS RESERVED  
COPYRIGHT 2026 DELFIN S.R.L. ALL RIGHTS RESERVED

MACHINE CODE	DESCRIPTION
LC1000D-001	LABCONTROL 1000D

All data mentioned in this document may change without notice. All data contained in this document is subject to change without notice.

**DELFIN**  
FOR A DUST-FREE WORLD

www.delfinvacuums.com  
delfin@delfinvacuums.it