

XTRACTOR 75 AF

INDUSTRIAL VACUUM CLEANER FOR FINE DUST FOR SURFACE TREATMENT



Filter category:

FEATURES

- Fine dust
- Compact and mobile
- Complete painted steel construction
- PTFE filter, class M with reverse air pulse automatic filter cleaning
- Endless Bag system for safe dust collection

All data mentioned in this document may change without notice. All data contained in this document is subject to change without notice.

DELFIN
FOR A DUST-FREE WORLD
www.delfinvacuums.com
delfin@delfinvacuums.it

TECHNICAL DATA

		XTRACTOR75AF-001
Voltage	V	400
Power	kW	8.6
Frequency	Hz	50
Current draw	A	15.5
Suction inlet diameter	mm	80
Tank capacity	L.	100 / Endless Bag 20 m
Noise level	dB(A)	76
Dimensions	cm	78x127x178h
Weight	kg	215
Electrical protection	IP	65
Maximum vacuum	mmH2O	4000
Minimum vacuum	mmH2O	2700
Continuous waterlift	mmH2O	2900
Maximum air flow	m ³ /h	700
Motor Type		Three-phase Turbine
Primary filter		Cartridge
Number of cartridges		4
Primary filter load	m ³ (m ² /h)	88
Primary filter surface area	cm ²	80000
Primary filter media		Polyester
Filter class (IEC 60335-2-69) primary filter		M PTFE
Filter cleaning system		PN - automatic compressed air filter cleaning system during
Absolute HEPA Filter		Optional
Filter area of the absolute filter	cm ²	52000
Absolute filter class (EN 1822-5)		H14 with 99.995% efficiency according to the MPPS method
Pressure relief valve		Included

MACHINE CODE	DESCRIPTION
XTRACTOR75AF-001	XTRACTOR 75 AF LP 20MT With compressor

OPTIONAL

Code	Description
H	Additional H14 absolute filter



COPYRIGHT 2026 DELFIN S.R.L. ALL RIGHTS RESERVED
COPYRIGHT 2026 DELFIN S.R.L. ALL RIGHTS RESERVED

DELFIN
FOR A DUST-FREE WORLD

www.delfinvacuums.com
delfin@delfinvacuums.it

All data mentioned in this document may change without notice. All data contained in this document is subject to change without notice.